

DISPLAY

AVAILABLE COLORS



Silver



Black



SHOWN IN BLACK

KEY FEATURES

- 32" Pro Series True-Outdoor All-Weather LED-LCD display for permanent outdoor installation
- Bright 32-inch full HD, 1080p LED-LCD screen for improved outdoor viewing
- Direct Sunlight-Readable
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic backout
- Exterior designed to protect internal components from rain, snow, dust, insects, humidity, and salt air.
- Powder-coated rust-proof aluminum exterior for strength and durability.
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 122 degrees F.
- Ability to operate in cold weather (-40 degrees F).
- Front tempered anti-reflective glass window provides added protection to LED-LCD screen, and safeguards against vandalism and abuse.
- RS232 serial control with discrete on, off, and input control.
- Rear IR receiver (located in the cable-entry compartment).
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups.
- Optional water-tight media player/cable compartment accommodates a variety of media players including Brightsign[®]
- Weatherproof detachable 20W speaker module (not-included), remote control, and control buttons.
- Side control button lock-out prevents unauthorized users from changing the programming.
- Includes warranty and manual
- Portrait installation only. (For Landscape installation see SB-3214HD).

<p>SCREEN</p>	<p>SCREEN 31.5-inch Diagonal Color Active Matrix TFT LED-LCD</p> <p>RESOLUTION 1920 x 1080 Full-HD 1080p</p> <p>ASPECT RATIO 16:9</p> <p>CONTRAST RATIO 1400:1</p>	<p>FRAME RATE 60 Hz</p> <p>VIEWING ANGLE 178° x 178°</p> <p>RESPONSE TIME 6.0 milliseconds</p> <p>TV FORMATS 1080p, 1080i, 720p, 720i, 480p, 480i</p>
<p>CONNECTIONS</p>	<p>RF Antenna/CATV (ATSC/QAM/NTSC) x1</p> <p>HDMI HDMI™ Input x2</p> <p>VIDEO COMPOSITE S-Video x1 and Composite Video x1, L/R Audio Inputs x1</p> <p>VIDEO COMPONENT YPbPr plus Stereo Audio x2</p> <p>PC 15-pin D-sub VGA plus Stereo Audio</p>	<p>CONTROL SET RS232 Serial, Discrete IR Control, Concealed IR Window</p> <p>AUDIO OUT Digital SPDIF Audio(fixed) Analog 1/8" headphone jack (variable)</p> <p>SPEAKERS 20 WATT detachable speaker module(not included)</p> <p>INPUT POWER 100-240 VAC, 50-60 Hz 2.0 A Max (0.5 A @ 120V)</p>
<p>TEMPERATURE TOLERANCES</p>	<p>OPERATING TEMP -40° to 122° F. (-40° to 50°C.)</p> <p>NON-OP. TEMP -40° to 140° F. (-40° to 60°C.)</p> <p>(OFF MODE WITH POWER APPLIED) The non-operating temperature feature requires power to be applied.</p>	
<p>PHYSICAL SPECS</p>	<p>ACCESSORIES INCLUDED Weatherproof remote control</p> <p>EXTERIOR Powder-coated aluminum.</p> <p>EXTERIOR COLORS Black, Silver</p> <p>TV DIMENSIONS 20.02 W x 32.07"H (34.17"H with speaker) x 6.29"D</p> <p>TV WEIGHT 41.0 lbs (45.0 lbs with speaker module)</p>	<p>SHIPPING DIMENSIONS 37.0"W x 32.0"H x 12.0"D</p> <p>SHIPPING WEIGHT 59.0 lbs</p> <p>RESIDENTIAL WARRANTY Two-year parts and labor.</p> <p>COMMERCIAL WARRANTY Two-year parts and labor.</p> <p>MOUNT PATTERN 100mm x 100mm or 400 x 200mm</p>